



Specifications

Bone Dry Plus Penetrating Sealer

Description

Bone Dry Plus penetrating concrete sealer is a permanent penetrating concrete sealer with added antimicrobial additive mixed into the product. With added antimicrobial protection Bone Dry Plus prevents mold and mildew from forming in the pores of the concrete slab. This allows any surface mold or mildew to be easily removed from the concrete surface. Bone Dry Plus is easy to apply using a pump sprayer. Our Plus sealer can be applied to new and existing concrete surfaces and can be applied underneath or over the surface of any Portland cement based concrete patch. Our water based product solidifies to fill the pores below the surface of the concrete slab preventing moisture from reaching the surface. Bone Dry Plus can be applied to interior and exterior concrete slabs including slab on grade, slab on deck, garages, driveways, patios and porches, sidewalks, and concrete pavers. When used with our Bone Dry Primer our Plus sealer can be also used over extremely porous concrete block walls.

Finished Flooring and PH Protection

Bone Dry Plus sealer protects finished flooring from concrete slabs containing high relative humidity (RH) readings reaching up to and beyond 99% as well as calcium chloride readings reaching 25 lbs. Bone Dry Plus protects adhesives from re-wetting causing finished flooring to delaminate from the concrete surface. This sealer prevents concrete moisture from causing finished flooring failures such as bubbling, discoloration, cupping and bowing, peeling from the surface and other concrete moisture related failures.

Exterior Protection

Bone Dry Plus increases the density of concrete extending the life of the concrete slab. It protects exterior slabs and garages from outside elements and salts from penetrating and deteriorating the concrete. Our sealer prevents moisture from penetrating into the concrete which causes aggregate to expand and damage the surface of the slab. Our sealer also protects the slab from becoming damaged in freeze/thaw conditions in colder climates.

Mold and Mildew Protection

Bone Dry Plus with its added antimicrobial protection prevents harmful mold and mildew from growing in your concrete slab causing allergy irritation, harmful conditions, and bad odors.

Concrete Floor Preparation

Remodeled Concrete Surfaces

Bone Dry Plus sealer must be applied to a clean, porous concrete surface in order to penetrate and react to create a strong barrier. Existing concrete surfaces with prior surface coatings must either receive a top coating of concrete (self leveler, skim coating) or be mechanically profiled with a diamond grinding or shot blasting machine in order to achieve a clean, porous surface. Major floor leveling and skim coating must be completed using a Portland cement based product and be completed prior to applying the Plus sealer. Minor patching and skim coating can be completed after the sealer is applied. Gyp-Crete is prohibited from being used with this sealer. Concrete slabs with known moisture related issues and over 20 years of age must receive a skim coating of Portland cement based concrete prior to applying the Bone Dry Plus sealer. **Contact Bone Dry Products** for exceptions to this requirement.

New Concrete Slabs

All construction material and debris (dust, paint, drywall mud, etc.) must first be scraped or broom swept from the surface of the slab. If a slab has received a hard troweled finish, our Etch-a-Crete must be applied or the surface must be mechanically

profiled to open the pores of the slab. Major floor leveling and skim coating must be completed using a Portland cement based product and be completed prior to applying the Plus sealer. Minor patching and skim coating can be completed after the sealer is applied. Gyp-Crete is prohibited from being used with this sealer.

Cracks and Trenches

Any existing cracks (expansion joints not included) with visible gaps must be filled and floated over with Portland cement 6 in. past the crack. Trenches must be floated over the saw cuts 6 inches onto the existing concrete.

Application

Protecting Finished Surfaces

Any finished surfaces such as cabinetry, glass, finished metal surfaces, and finished painted areas must be masked off with plastic up to 2 feet from the concrete to prevent over spray from causing discoloration. Painted areas affected by over spray can be repainted to address the discoloration.

Plus Sealer Application Instructions

Bone Dry Plus sealer can be applied using a pump or battery powered sprayer with a wide fan tip. In 1,000 to 2,000 thousand sqft sections, apply one coat of sealer so that the slab receives a darkened to light cloudy appearance. Let the area sit for **no more than** 10 minutes. Apply a second coat to the section while the first coat is still wet. Only apply a second coat in areas where the sealer has penetrated and the texture of the concrete has become visible. If a thick white pool appears on the slab use a broom or brush to spread the product. Once dry, the slab may have a cloudy appearance due to product solidifying on the surface. Contaminants from the slab may rise to the surface as well providing further discoloration.

Application Instructions at the Pour

During the pour, use a super plasticizer or other modifier as needed to increase workability while troweling. Do not use a cure and seal or water on the slab. Do not burnish the concrete when

troweling. Slab must be porous enough at the surface after troweling is completed to absorb moisture. After the final trowel has taken place, allow the slab to dry for a minimum of one hour and until the slab can be walked on without indenting the slab. Sealer is applied using a wide fan tip pump sprayer. Apply Sealer in 1,000-2,000 square foot sections. Allow sealer to absorb for 5-8 minutes. After 5-8 minutes apply a second coat in the areas that penetrated into the slab. Allow sealer to dry 6 hours prior to opening the slab to foot traffic. If installing finished flooring less than 30 days after pour contact bone dry for approval.

Spread

For broom trowel and mechanically profiled surfaces the spread for Plus sealer is 240 square feet per gallon. For hard trowel surfaced where the slab pores are opened with Etch-a-Crete the spread for Plus sealer is 300 square feet per gallon.

Adhesives

Adhesive Application

The sealed concrete surface must be clean and free of any construction dust and loose particles pushed to the concrete surface prior to applying adhesives. Adhesives applied directly to the sealed concrete surface must be applied as per specifications for a non-porous substrate.

Contact

Bone Dry Products

9009 58th Pl

Kenosha, WI 53144

262-694-9748

Email: info@bonedryproducts.com

Website: www.bonedryproducts.com

Warranty Information

Bone Dry Plus carries a manufacturer's limited warranty stating that this product is free of defects and covers only replacing the Bone Dry Product if there is a claim on the product.